# PINIACLE Water Treatment

### 5800 XTR2 Touchscreen Water Softener

When water quality matters, Pinnacle residential water softeners and filtration systems deliver.
Featuring Pentair's patented Fleck technology and backed by superior after-sales support, Pinnacle systems are designed with Canadian families in mind.

Enhance the quality of your water with the Fleck 5800XTR2 Touchscreen Water Softener.

- Silky soft skin & hair after showering
- Clothes are brighter, softer & last longer
- Glasses & dishware are spot free
- Use 50% less detergent, fabric softeners, soap, shampoo & personal moisturizers
- Add years of life to water heaters, dishwashers & washing machines

Water treatment solutions engineered for your unique water needs.



**FLECK®** 





## Fleck 5800XTR2 Residential Water Softener

### **FEATURES**

- Premium touchscreen LCD display
- 5-cycle programing
- Fast-positioning, reversible 10,000 RPM 12-volt DC drive motor
- Seal and spacer cartridge for easy servicing
- Precision cycle positioning
- Soft water refill for better brine saturation and cleaner brine tank
- Programming memory backup in case of power loss/outages

**System includes:** Control valve featuring XTR2 touchscreen, ¾" turbine water meter, ¾" MPT poly bypass assembly and Pentair poly glass media vessel with 1" ABS internal distribution.

**Softener includes:** High quality Structural mineral and brine tanks. Brine tank c/w salt shelf and Fleck 2310 brine safety float assembly. Uses high purity, premium grade cation exchange resin.



### **Specifications**

| Model<br>Number | Resin<br>(CuFt) | Tank Sizes |            | Unit Cap |     | Flow Rates |      | BKW   | Salt |    | Weight |
|-----------------|-----------------|------------|------------|----------|-----|------------|------|-------|------|----|--------|
|                 |                 | Resin Tank | Brine Tank | Min      | Max | Service    | Peak | (GPM) | 10   | 15 | (lbs)  |
| 24K58XTR2       | 0.75            | 8" x 44"   | 14" x 34"  | 18K      | 24K | 4          | 8    | 1.5   | 8    | 12 | 85     |
| 30K58XTR2       | 1.0             | 9" x 48"   | 14" x 34"  | 24K      | 30K | 5          | 10   | 2.0   | 10   | 15 | 95     |
| 40K58XTR2       | 1.3             | 10" x 47"  | 14" x 34"" | 32K      | 40K | 5.5        | 11   | 2.4   | 13   | 20 | 125    |
| 60K58XTR2       | 2               | 12" x 52"  | 18" x 40"  | 48K      | 60K | 6.5        | 13   | 3.5   | 20   | 30 | 170    |
| 90K58XTR2       | 3               | 14" x 65"  | 18" x 40"  | 72K      | 90K | 6.5        | 13   | 4.0   | 30   | 60 | 225    |

Capacities are based on resin manufacturer's data ● Units are set to the factory minimum salt setting ● Use minimum capacity when sizing ● Flow rates are in U.S. Gallons/minute ● Sizes and space requirements are in inches









