

PINNACLE

Water Treatment

9100TS Professional Water Treatment System

When water quality matters, Pinnacle residential water softeners and filtration systems deliver. Featuring Pentair's patented Fleck technology and backed by superior after-sales support, Pinnacle systems are designed with Canadian families in mind.

Enhance the quality of your water with the Fleck 9100TS Twin Alternating Water Softener with Advanced Sensor Technology.

- Silky soft skin & hair after showering
- Clothes are brighter, softer & last longer
- Glasses & dishware are spot free
- Use 50% less detergent, fabric softeners, soap, shampoo & personal moisturizers
- Add years of life to water heaters, dishwashers & washing machines

Water treatment solutions engineered for your unique water needs.




 **PENTAIR**
FLECK®



Fleck 9100TS Twin Alternating Residential/Light Commercial Water Softener

FEATURES

- Twin Tank Technology with Sensor Probes thrive in fluctuating water hardness delivering 24/7 Uninterrupted Soft Water
- Real-time water hardness data combined with an Intuitive Controller provides a "Set It and Forget It" approach
- Twin Tank Sensors + Upflow Brining+SSTC-6000 resin = the most efficient regeneration available
- 18-karat gold-plated sensor probes "Never Sleep", and reduce unnecessary regenerations
- Adaptive system adjusts to changes in the customers water use; no need for reserves and re-programming
- Soft water refill for cleaner brine tank, less maintenance and better regeneration performance



System includes: Control valve featuring 9100TS format, 3/4" turbine water meter, 3/4" FPT stainless bypass, 18-karat gold-plated sensor probes and Pentair poly glass media vessel with 1" ABS internal distribution.

Softener includes: High quality structural mineral and brine tanks. Brine tank c/w salt shelf and Fleck 2310 brine safety float assembly. Uses maximum efficiency Purolite SSTC-6000 cation exchange resin.

Specifications

Model Number	Resin (CuFt)	Tank Sizes		Unit Cap		Flow Rates		BKW (GPM)	Salt Req. (lbs.)	Weight (lbs.)
		Resin Tank	Brine Tank	Min	Max	Service	Peak			
24KSST9100TS	0.75	8" x 44"	14" x 34"	18K	24K	4	6	1.5	4.5	150
30KSST9100TS	1.0	9" x 48"	14" x 34"	24K	30K	5	8	2.0	6	175
45KSST9100TS	1.5	10" x 54"	14" x 34"	36K	45K	7.5	12	2.4	9	230
60KSST9100TS	2	12" x 48"	14" x 34"	48K	60K	10	16	3	12	300

Capacities are based on resin manufacturer's data • Units are set to the factory minimum salt setting • Use minimum capacity when sizing • Flow rates are in U.S. Gallons/minute • Sizes and space requirements are in inches.



www.pinnaclewater.ca



info@pinnaclewater.ca



519-843-4232



Pinnacle Water

SUMMIT
WATER

